

Cleaning and disinfecting steam equipment

NF EN ISO 13485

STEAM GENERATOR

<u>SP400</u>



TECHNICAL SPECIFICATIONS

 Boiler capacity 3.1 L material / guality stainless steel 316L steam pressure 5 bars steam temperature 150°C self-filling device yes steam outflow 0 à 70 g/mn Electric power 230v - 50/60Hz voltage boiler 2800w • internal, dismountable and anti-corrosion resistance total power 2850w Tanks capacity · water tank for steam production 4,6 L · filter on steam output yes Electric protection IP 44 product IP 56 waterproof electronic and electric box · Weight / size steam hose professional 4,5 m · electric cable in neoprene 10 m product 19 Kg size L 42 x | 30 x h 43 cm Homologation / certifications • CE medical devices LNE 0459 SANIVAP is certified : ISO 13485 • Warranty : 1 year (parts / labour and transportation local repair by accredited technician) cost or

Boiler warranty : 3 years according to Sanivap warranty conditions

The SP400 biocleaning steam system ensures the complete cleaning and disinfecting of all kind of surfaces : floors, vertical surfaces, furniture, equipment, medical devices... The constant steam quality of the SP400 ensures its effectiveness in terms of cleanliness and disinfection.

The SP400 is especially designed for intensive use **up to 8 hours per day**.

The SP400 steam system is ergonomic, easy to operate and very suitable for daily usage in accordance with SANIVAP protocols. The wide range of adaptable accessories contributes to its effectiveness and versatility.



Parc d'activités – 69280 Sainte Consorce - FRANCE Tel : 00.33.437.225.555 – Fax : 00.33.437.225.556 Info@sanivap.fr - www.sanivap.fr



Cleaning and disinfecting steam equipment

SP400

STEAM QUALITY

Conception of the boiler

- Internal, dismountable and anti-corrosion résistance
- Quality material (316L austenitic stainless steel)
- Self filling magnetic system
- High boiler insulation
- Optimized performance ratios of the boiler : power / pressure / steam outflow

□ Conception of fluid circuits

- Electronic monitoring of steam pressure and temperature to secure disinfection efficacy.
- Steam output regulation 6 levels
- Steam stainless steel filter protecting electro valve
- Self-filling magnetic contactor
- Filter on water tank
- Easy drain of the boiler with safety valve
- Easy drain of water tank

PRODUCT QUALITY

□ Quality of material

- Structure and components in stainless steel , ABS, Aluminium
- Stainless steel boiler 18/10 quality AISI 316L
- Wheels high quality standard

□ Safety

- Hand contactor on steam handle
- Device fully protected IP 44
- Electric and electronic box waterproof IP 56
- Neoprene electric cable 10m (3x2.5mm)
- Alarm : lack of water for boiler supply
- Lack of water security for boiler protection

Ergonomics

- Ergonomic hand contactor on steam handle
- Ergonomic steam handle
- Easy accessories connexion
- Easy draining and steam cleaning of water tank
- Range of ergonomic accessories
- Ergonomic steam biocleaning trolley
- LCD control screen for operator (steam output, water level in tank...)



Ergonomic steam hose and handle



Sensitive switches and LCD control screen

- **PROTOCOLS AND TRAINING**
- Training provided for use of the steam system and its regular maintenance
- Suitable protocols at disposal

TECHNICAL ASSISTANCE

• Technical assistance to the users for an optimal use of the steam system

Availability of maintenance contracts

 After Sales Service provided by accredited national network

ACCESSORIES RANGE

•The SANIVAP long experience has enabled to develop a wide range of ergonomic accessories suitable for cleaning and disinfecting protocols.

•The technical microfiber range associated to the SANIVAP accessories optimizes the performance of the steam system.

STANDARD EQUIPMENT

SP400KIT:

SP400:

SV250 : Floor Steam MOP

Flexible steam hose 4,5 m SP45 Refill can - sealing kit

SP400 + Bio cleaning trolley SP150 Accessories kit : SP200+ SP220 SP230 + SP240 + SP250



SP200 : Bent steam nozzle



SP220: Brush 20cm SP230: Brush + rubber wiper



SP240: Microfiber mount